

PERFECT COAT CPF - 904

친환경 수용성 발수제

WALLS WATER REPELLENT WATERPROOFING

CHEMPROOF

Waterproofing System

● 특징

CPF - 904는 동결이나 염 등 다양하게 발생할 수 있는 외부적인 손상 요인의 근원을 차단하여, 건축물의 통기성은 유지하고 건물이 오래도록 최적의 상태를 유지할 수 있도록 하며, 냄새가 없고 화재 위험성이 전혀 없는 친환경 제품으로 내구성이 월등하며 수성페인트 작업 후 도포 시 페인트의 들뜸 및 변색을 방지할 수 있는 제품입니다.

● 용도

- 내 외부 콘크리트, 적벽돌, 목조주택, 황토주택, 석재건물, 타일건물 등 외벽 발수용

● 특성

- 우수한 통기성, 침투 조밀성
- 유기용가 첨가되지 않은 친환경 제품
- 도포성이 우수하고 건조 후 표면이 투명하여 기존 색상 보존
- 도포 후 시간경과에 따라 물성증가로 인한 방수성능 향상

● 주의사항

- 3년 이내 유성 발수제 작업이 있는 경우 작업을 피하십시오.
- 시공부위를 최대한 건조 시켜주십시오.
- 시공 후 12시간 이내에 물 접촉을 피하여 주십시오.
- 5°C 이상 30°C 이하에서 시공하여 주십시오.
- 어린이 손에 닿지 않는 곳에 보관하고 실내에 보관하십시오.

● 사용방법

1. 시공부위에 묻어있는 기름, 이끼, 유분, 오물찌꺼기 등은 깨끗이 청소합니다.
- 청소 시 산성분이 있는 세척제는 사용하지 않도록 합니다.
- 표시공부위에 물기가 있을 경우 반드시 건조 후 시공합니다.
- 백화가 발생된 부위는 Sand Paper (100방) 또는 거친 마대를 사용하여 벗겨냅니다.
2. 시공부위 주변의 유리창, 자동차 및 식물 등은 반드시 비닐 보양작업을 하여 시공시 발수제가 묻지 않도록 합니다.
3. 부실부위 및 크랙이 0.3mm 이상인 경우 씰링제, 코킹작업 등으로 보강합니다.
4. CPF - 904 사용 시 물로 희석하여 사용하여서는 안되며, 반드시 원액을 사용하여야 합니다.
5. 에어리스, 롤러, 붓 등으로 흘러 내릴 정도로 분사, 도포합니다.

● 포장단위 / 색상

- 4Liter, 18Liter Pail / 색상 : 유백색 건조 후 투명



● Feature

CPF - 904 blocks the source of external damage factors such as freezing and salt, so that the building can maintain its breathability and maintain its optimum condition for a long time. It is an eco-friendly product with no odor, no fire hazard, and superior durability. It is a product that can prevent paint discoloration when applying after water paint work.

● Uses

- Exterior concrete, red brick, wooden house, other house, stone building, tile building, etc.

● Characteristic

- Excellent breathability, penetration / - Eco-friendly products
- Excellent applicability. After drying, the surface is transparent, preserving the original color
- Improved water resistance due to increased physical properties over time after application

● Precautions

- Avoid use if you have done oil-based water repellent work within 3 years.
- Please dry the construction site as much as possible.
- Avoid contact with water within 12 hours after application in wet condition.
- Please apply at 5 °C or more and 30 °C or less.
- Please keep out of reach of children and Please keep it inside.

● How to use

1. Clean the construction site thoroughly. (Such as oil, moss, oil, debris, etc.)
- Do not use cleaning agents containing acidic substances during cleaning.
- If there is any water, it must be dried before construction.
2. Glass windows, automobiles, and plants around the construction site must be covered with vinyl or cloth so that the water repellent does not touch the construction site.
3. If the crack area is 0.3mm or more, it must be reinforced by sealing and caulking work.
4. When using the walls coat, do not dilute with water. You must use the undiluted solution.
5. Spray and apply enough to flow down to airless, roller, brush.

● Packing Unit & Color

- 4Liter, 18Liter Pail / Color : White. (Transparent after drying)



* For further information, please refer to Material Safety Data Sheet (MSDS).
* 기타 상세한 자료는 물질안전보건자료 (MSDS)를 참조하십시오.

Supplier in Myanmar



Yangon Branch : Room No. 6C, Aye Yeik Thar Condominium, No. (483) ,
Aye Yeik Thar (2) Street, Bahan Tsp. Yangon, Myanmar

MP : 09-44476-7044 (Myanmar & English)
MP : 09-44476-7045 (Korean & English)



16gil - 6 Jinjang Bukgu, Ulsan, Korea
Tel : 82-52-298-2259 , Direct MP : 82-10-9300-2259
E-mail : steve@ghi.cc Myanmar MP : 09-42173-9844 (Korean)



PERFECT COAT CPF - 904

친환경 수용성 발수제

WALLS WATER REPELLENT WATERPROOFING

CHEMPROOF

Waterproofing System

● Feature

CPF-904 သည် အဆောက်အအုံပြင်ပရိုတက်ရှင်များအား ရာသီဥတုဒဏ်ကို ကြာရှည်စွာ ပိုမိုခိုင်စေရန် ရည်ရွယ်၍ ထုတ်လုပ်ထားသော Wall Water Repellent ဖြစ်ပါသည်။ ဈေးနှုန်းသက်သာပြီး အနံ့မရှိခြင်း၊ ကြာရှည်ခံနိုင်ခြင်းတို့ကြောင့် ၎င်းအား အသုံးပြုခြင်းဖြင့် မိမိအဆောက်အအုံ၏ မူလသုတ်ထားသော ရေဆေးအရောင်အား နှစ်ပေါင်းကြာရှည်စွာ စွဲမြဲစေပါသည်။

● Uses

- ကွန်ကရစ်အပြင်နံရံများ၊ အုတ်နံရံများ၊ သစ်သားအိမ်နှင့်နံရံများ၊ ကျောက်ဖြင့်ဆောက်လုပ်ထားသော အဆောက်အအုံများ၊ ကြေးပြားဖြင့် ဆောက်လုပ်ထားသော အဆောက်အအုံများတွင် အသုံးပြုနိုင်ပါသည်။

● Characteristic

- အနံ့ကင်းမဲ့ခြင်း၊ ဈေးနှုန်းသက်သာခြင်း။
- အသုံးပြုရလွယ်ကူခြင်း၊ ခြောက်သွေ့သွားသည်နှင့် မျက်နှာပြင်သည် ကြည်လင်လာကာ အောက်ခံမူလအရောင်အတိုင်း ပြန်ရခြင်း။
- ရေခိုဒဏ်ခံနိုင်မှုကောင်းခြင်း။ (Water Resistance)

● Precautions

- လွန်ခဲ့သော နှစ်အတွင်း အောက်ခံဆီဆေး အသုံးပြုထားလျှင် CPF-904 ကို အသုံးမပြုပါနှင့်။
- လုပ်ငန်းခွင်နေရာအား ခြောက်သွေ့အောင်ထားပါ။
- အသုံးပြုပြီး ၁၂ နာရီအတွင်း ရေမထိရပါ။
- 5°C အထက် နှင့် 30°C အောက်တွင် အသုံးပြုပါ။
- ကလေးများနှင့် ဝေးရာတွင်ထားပါ။ အဆောက်အအုံအတွင်း၌သာ သိမ်းဆည်းပါ။

● How to use

1. လုပ်ငန်းခွင်နေရာအား ဆီများ၊ ဖန်မှုန့်များ၊ အမှိုက်သရိုက်များ မရှိအောင် သေသေချာချာသန့်ရှင်းပါ။ သန့်ရှင်းရာတွင် အက်ဆစ်ပါသော cleaning agent များကို အသုံးမပြုရ။ လုပ်ငန်းခွင်နေရာတွင် ရေများရှိပါက CPF-904 အသုံးမပြုမီ ဦးစွာ ခြောက်သွေ့အောင် ပြုလုပ်ပါ။
2. Construction site ပတ်ဝန်းကျင်ရှိ ပြတင်းပေါက်များ၊ စက်ပစ္စည်းများ၊ စက်ရုံများအား vinyl ဖြင့် ကာရံထားပါ။
3. 0.3mm ထက်ပိုသည့် အက်ကြွကြောင်းများရှိလျှင် sealant ဦးစွာ ဖြည့်ပါ။
4. CPF- 904 တစ်မျိုးတည်းသာ အသုံးပြုပါ။ ရေနှင့် ရောနှောခြင်းမပြုရ။
5. Brush (သို့) Roller (သို့) airless spray တို့ကို အသုံးပြု၍ CPF-904 ကို လိုလုံလောက်လောက် ထည့်သုံးနိုင်ပါသည်။

● Packing Unit & Color

- 4Liter, 18Liter Pail / Color : White. (Transparent after drying)

● Feature

CPF - 904 is blocks the source of external damage factors such as freezing and salt, so that the building can maintain its breathability and maintain its optimum condition for a long time. It is an eco-friendly product with no odor, no fire hazard, and superior durability. It is a product that can prevent paint discoloration when applying after water paint work.

● Uses

- Exterior concrete, red brick, wooden house, ocher house, stone building, tile building, etc.

● Characteristic

- Excellent breathability, penetration / - Eco-friendly products
- Excellent applicability. After drying, the surface is transparent, preserving the original color
- Improved water resistance due to increased physical properties over time after application

● Precautions

- Avoid use if you have done oil-based water repellent work within 3 years.
- Please dry the construction site as much as possible.
- Avoid contact with water within 12 hours after application in wet condition.
- Please apply at 5 °C or more and 30 °C or less.
- Please keep out of reach of children and Please keep it inside.

● How to use

1. Clean the construction site thoroughly. (Such as oil, moss, oil, debris, etc.)
 - Do not use cleaning agents containing acidic substances during cleaning.
 - If there is any water, it must be dried before construction.
2. Glass windows, automobiles, and plants around the construction site must be covered with vinyl or cloth so that the water repellent does not touch the construction site.
3. If the crack area is 0.3mm or more, it must be reinforced by sealing and caulking work.
4. When using the walls coat, do not dilute with water. You must use the undiluted solution.
5. Spray and apply enough to flow down to airless, roller, brush.

● Packing Unit & Color

- 4Liter, 18Liter Pail / Color : White. (Transparent after drying)



* For further information, please refer to Material Safety Data Sheet (MSDS).
* 기타 상세한 자료는 물질안전보건자료 (MSDS)를 참조하십시오.

Supplier in Myanmar



Yangon Branch : Room No. 6C, Aye Yeik Thar Condominium, No. (483) ,
Aye Yeik Thar (2) Street, Bahan Tsp. Yangon, Myanmar

MP : 09-44476-7044 (Myanmar & English)
MP : 09-44476-7045 (Korean & English)



16gil - 6 Jinjang Bukgu, Ulsan, Korea
Tel : 82-52-298-2259 , Direct MP : 82-10-9300-2259
E-mail : steve@ghi.cc Myanmar MP : 09-42173-9844 (Korean)

